

Navlam

How to Specify

Below you will find a specification form template to help you specify our New Age Veneers – Navlam Timber Veneer range. Please highlight and copy and paste the relevant details into your specification sheet. You can add other clauses as appropriate.

Contact –

New Age Veneers. Unit 14, 22-24 Beaumont Road
Mount Kuring-Gai 2080 NSW Australia

T: +61 2 9457 7169

F: +61 2 9457 9644

E: enquiries@newageveneers.com.au <insert your local reps name and mobile number>

Navlam Timber Veneer –

Navlam Timber Veneer is to be New Age Veneers – Navlam Sandblasted (or) Polyurethane <insert veneer name> Pre Finished Veneer <can also include substrate (MR MDF) and thickness (16mm)>

Grain direction –

as indicated on the drawings (with crown cut veneers note the direction and location of the crowns). Please note, Navlam cannot be supplied horizontally laid up on board.

Backing –

Navlam board to be backed with a balancing veneer back <face grade / down grade / BAMO (back at manufacturer's option)>

All Balancing backs are to be 1.2mm White or Black. If not used voids Warranty.

Edges –

Edges to be finished with a (1mm / 2mm / other)* matching ABS edging.

Finishing –

Navlam is a pre finished veneer, therefor dose not require any additional polishing. Please make a note for cabinetmaker/joiner to leave protective plastic film in-tacked until fully installed, and all trades are finished.

